

HOLDER

HOLDER TRACTORS INC.

HOLDER SERIES Model C70



HOLDER

HOLDER TRACTORS INC.

SPECIFICATIONS

ENGINE: Kubota 4-cylinder 4-stroke turbo diesel, Tier 4 final
Displacement - 160 in³ / 2615 cm³
Power - 48 kW (65 HP)
Torque - 165 lbf-ft / 225.0 Nm
Rated speed - 2400 Rpm
Cooling - Water cooling
Fuel tank capacity - 17 Gal / 65 l

DRIVE: Hydrostatic traction drive, controlled digital-electrically, stepless road speed control, suspended front and rear axle; PowerDrive via four wheels of the same size

DIFFERENTIAL LOCK: Mechanical at the front and rear, simultaneously switchable electrohydraulically, acts on both axles at 100

MAXIMUM SPEED: 25 Mph / 40 km/h

PTO SHAFTS: Optional: power-switchable, independent PTO shaft, can be switched separately at the front and rear
Front: mechanically powered, 1000 Rpm or optionally 540 Rpm
Rear: hydraulically powered, 540 Rpm
Size: 1 3/8 inches

BRAKES: Hydraulically actuated four-wheel brake, electrically actuated stop brake on the front axle

HYDRAULICS: Hydraulic pump 9 US gpm / 35 l/min optionally extendable with additional device variable displacement pump 19 US Gpm / 70 l/min

- Rotopac body 25 cubic yards
- Rear tailgate 2 cubic yards
- 12 foot Automated arm
- Auger assembly
- Welded auger shaft
- Fire extinguisher (10 lbs) and Flare kit
- Shovel & Broom rack
- Lateral hydraulic loading panel
- 4 Camera System ZD

3 ATTACHMENT AREAS

Front and rear lifts as well as 3rd attachment point over engine.
Easy attachment mounting, one-person and no tools required.



© Max Holder GmbH 2013