

2017 Peterbilt 348 Cable-Hoist Roll-Off with Roll-Rite DC350 Tarp Package



SPECIFICATIONS

KEY FEATURES / KEY SPECS

VEHICLE DETAILS

- Model 348 medium duty
- Paccar PX – 9 engine 330 HP @ 2000 RPM
- Allison 3500 RDS transmission
- FGAWR 18,000 lbs, RGAWR 20,000 LBS per axle, GVWR 58,000 LBS

PALFINGER CABLE-HOIST ROLL-OFF

- 60,000 LBS capacity
- Max dump angle 50 degrees
- 12' – 22' Container length range
- 8" x 4" x 3/8" main frame 4" x 3" x 1/4" sub frame
- Dual inboard single stage lift cylinders (eliminates interference with outboard chassis components & allows for multiple lift axle installations)
- Five sets of outside basket style side rollers w/high carbon pins
- 7/8" EIPS 6 x 37 domestic cable, fixed length, needs no adjustment w/1 1/4" pear loop
- Automatic front left & right container straps & locks
- Manual nylon strap winch rear container hold downs
- Patented automatic folding ICC bumper
- Aluminum fenders
- Frame mounted tool box

ROLL-RITE DC350 ELECTRONIC / HYDRAULIC TARP SYSTEM

- Premium HD mesh tarp 96" x 28" floats over load
- Work lights
- Wireless remote key fob
- System weight – 800 lbs
- Patented sliding pivot set
- Super duty gear motor with 98" tarp spool with integrated housing
- Adjustable tower

