



SPX FLEXITRAX P550c





FLEXITRAX P550c

Portable video inspection for drainage, water and plumbing networks

KEY FEATURES / KEY SPECS

Battery Capacity

- Internal Li-Ion Battery (4S2P) - 14.68V, 6.4Ah (93.95WH)
- Battery run-time 7.5hrs view only/ 5hrs continuous recording

Connectivity

- USB 2.0 (x3), HDMI video out, analog video in (PAL/NTSC), headphones out, microphone in, rod/camera/drum connectivity and 802.11 b/g/n WiFi
- Basic reports, MSCC3 & 4: docx, MSCC5: docx or Xml, WinCan: Xml, Video: MP4, Image: JPEG

Construction

- High impact ABS and powder-coated, zinc-plated mild steel

Controllers

- Flexitrax P550c command module with integrated joysticks to control the camera and crawler
- Optional pendant controller for deployment phase

Dimensions/Weight

- 17.5" x 15.2" x 6.1"/445mm x 385mm x 155mm
- 16lb /7.25 kg

Display

- 12.1"/307mm, 1280 x 800 color LCD
- Recording format - Video: H.264. Audio: MP3. File format: MP4

KEY FEATURES / KEY SPECS CONTINUED

Drums

- Manual drum or powered drum, with cable length options from 500' to 1000'/150m to 305m

Power

- Power from drum, external mains PSU or internal battery
- Input requirements 10-30V, 60W
- Mains input 100-240VAC, 50-60Hz, 1.7A DC output 16V, 3.75A, 60W



PARTS / SALES / SERVICE / RENTALS
866 962 1218 westvac.com

