

KÄRCHER

KARCHER S75

STOCK #E013805



Acheson, AB
26609 111 Ave
T7X 6E1
T 780-962-1218
F 780-962-2230

Calgary, AB
3534 48 Ave SE
T2B 3L6
T 403-272-1334
F 403-272-1584

Surrey, BC
107, 9488 189 St
V4N 4W7
T 604-455-0084
F 604-455-0086

Saskatoon, SK
100, 3926 Burrton Ave
S7P 0E1
T 306-975-9400
F 306-975-9404

Winnipeg, MB
2, 1830 Dublin Ave
R3H 0H3
T 204-953-6644
F 204-633-4878

KÄRCHER

BUILD SPECIFICATIONS

- Engine (74 HP) Deutz TCD 3.6 4-cylinder common rail turbodiesel Stage V Emissions No DEF required.
- Fuel tank 84 l (18 gal)
- Infinitely variable DUAL DRIVE traction drive system (combination of hydrostatic and mechanical drive) with permanent all-wheel drive and electronic load limit control
- Speed Driving speeds 0–40 km/h (0-25 mph) (fast gear)/0–20 km/h (0-12 mph) (slow gear); working speed 0–15 km/h (0-9 mph) (fast gear) /0–8 km/h (0-5 mph) (slow gear)
- Differential lock Front and rear mechanical with 100% locking effect
- Parking brake Electric parking brake, active on both axles
- Speed Switchable from 540 to 1,000 rpm at 1,700 rpm engine speed
- Tandem pump volume flow controlled from the cab, circuit independent of steering and lifting functions
- Hydraulic control units Up to 4 double-acting control units
- Hydraulic couplings Up to 3 pairs of couplings at the front/up to 1 pair of couplings at the rear
- Hydraulic tank 34 l (7 gal) with fill level sensor
- Front power lift CAT II, double-acting, with floating position and vibration damping system, optional electro-hydraulic implement release, hydraulic side and incline adjustment
- Lifting force 2,700 kg (5952 lb)
- Unladen weight 3,100 kg (6834 lb)
- Total permissible weight 5,500 kg (12125 lb)
- Permissible axle load Front: 3,200 kg (7055 lb) Rear: 3,200 kg (7055 lb)
- Towing capacity Unbraked: 2,500 kg (5512 lb) Overrun braked: 4,500 kg (9921 lb)
- Wheelbase 1,827 mm (72 in)
- Total length incl. front power lift 3,750 mm (148" in)
- Total height 2,270 mm (89 in)
- Total outer width 1,310 mm (52 in)
- Turning circle radius outside 7,000 mm (276 in)

